

SMK23U / RU

Pattresses for use with Mains Smoke and Heat Alarms



DESCRIPTION

SMK23U – Pattress for surface installation of all Kidde and Firex mains alarms

SMK23RU – Relay Pattress for surface installation of all Kidde and Firex mains alarms

KEY FEATURES

SMK23U

- **Surface mounted** – fits all Firex alarms and Kidde mains CO alarms – 423/9HIR and 423D/9HIR
- **Easy to fit** – for convenient installation, particularly suitable for retrofit

SMK23RU (Relay version)

- **Volt-free contacts** – SPDT, rating 8A, 24V DC/230V
- **Response / Release time** – 500msec / 150msec

WHERE TO USE

For surface installations involving cable entry via trunking or conduit. The SMK23RU can be used, via a suitable relay control, to trigger auxiliary devices such as door closers, warning lights, horns and suitable warden-call systems. This pattress is not suitable for the 423/9HIR and 423D/9HIR CO alarms.

GENERAL FEATURES

Model	SMK23U / SMK23RU
Power Supply	230V mains-powered
Temperature Range	0°C to + 40°C
Humidity Range	Up to 93% Relative Humidity (RH) non-condensing
Pattress Dimensions	130 x 130 x 20mm / 130 x 130 x 20mm
Pattress Weight	120g / 120g
Warranty	6 years
Approvals	CE tested and certified



OPTIONAL PRODUCT

For installers of Firex mains alarms the following Firex-specific pattress may be used:

SMK4896 For surface installations involving cable entry via trunking or conduit with loose-fit terminal block for ease of installation

For further information see **SMK4896** datasheet.

SMK23U / RU

Pattresses for use with Mains Smoke and Heat Alarms



DESCRIPTION

SMK23U – Pattress for surface installation of all Kidde and Firex mains alarms

SMK23RU – Relay Pattress for surface installation of all Kidde and Firex mains alarms

NOTES

Notes section with horizontal lines for writing.

PACKAGED SPECIFICATIONS

	PLAIN BOX	PLAIN BOX
Order Code	SMK23U	SMK23RU
Pack Dimensions	135 x 135 x 22mm	135 x 135 x 22mm
Pack Weight	125g	125g
UPC Barcode	0-254177-230009	0-254177-231006
Case Quantity	6	6
Case Dimensions	145 x 145 x 150mm	145 x 145 x 150mm
Case Weight	0.8Kg	0.8Kg
ITF Outer Code	n/a	n/a